

---

Subject: Re: PHPBB smtp  
Posted by [jnz](#) on Wed, 12 Jul 2006 22:11:54 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

try this...

```
<?php
function mymail($to,$subject,$message,$headers)
{

    // set as global variable
    global $GLOBAL;

    // get From address
    if ( preg_match("/From:.*?[A-Za-z0-9\._%-\+]\@[A-Za-z0-9\._%-\+].*/", $headers, $froms) ) {
        preg_match("/[A-Za-z0-9\._%-\+]\@[A-Za-z0-9\._%-\+]/", $froms[0], $fromarr);
        $from = $fromarr[0];
    }

    // Open an SMTP connection
    $cp = fsockopen ($GLOBAL["SMTP_SERVER"], $GLOBAL["SMTP_PORT"], &$errno, &$errstr,
1);
    if (!$cp)
        return "Failed to even make a connection";
    $res=fgets($cp,256);
    if(substr($res,0,3) != "220") return "Failed to connect";

    // Say hello...
    fputs($cp, "HELO ".$GLOBAL["SMTP_SERVER"]."\r\n");
    print $GLOBAL["SMTP_SERVER"];
    $res=fgets($cp,256);
    if(substr($res,0,3) != "250") return "Failed to Introduce";

    // perform authentication
    fputs($cp, "auth login\r\n");
    $res=fgets($cp,256);
    if(substr($res,0,3) != "334") return "Failed to Initiate Authentication";

    fputs($cp, base64_encode($GLOBAL["SMTP_USERNAME"])."\r\n");
    $res=fgets($cp,256);
    if(substr($res,0,3) != "334") return "Failed to Provide Username for Authentication";

    fputs($cp, base64_encode($GLOBAL["SMTP_PASSWORD"])."\r\n");
    $res=fgets($cp,256);
    if(substr($res,0,3) != "235") return "Failed to Authenticate";

    // Mail from...
```

```
fputs($cp, "MAIL FROM: <$from>\r\n");
$res=fgets($cp,256);
if(substr($res,0,3) != "250") return "MAIL FROM failed";

// Rcpt to...
fputs($cp, "RCPT TO: <$to>\r\n");
$res=fgets($cp,256);
if(substr($res,0,3) != "250") return "RCPT TO failed";

// Data...
fputs($cp, "DATA\r\n");
$res=fgets($cp,256);
if(substr($res,0,3) != "354") return "DATA failed";

// Send To:, From:, Subject:, other headers, blank line, message, and finish
// with a period on its own line (for end of message)
fputs($cp, "To: $to\r\nFrom: $from\r\nSubject: $subject\r\n$headers\r\n\r\n$message\r\n.\r\n");
$res=fgets($cp,256);
if(substr($res,0,3) != "250") return "Message Body Failed";

// ...And time to quit...
fputs($cp,"QUIT\r\n");
$res=fgets($cp,256);
if(substr($res,0,3) != "221") return "QUIT failed";

return true;
}
?>
```

it justs opens a connection and sends the data through it.

dan

---